

Applications:

- Forestry
- Landscaping
- Site preparation
- Composting
- Crop residue mulching

Functions:

- Slash reduction
- Recreating trails
- Land clearing
- Soil preparation for new growth
- Grinding stumps
- Grinding standing trees
- Eradicating undesirable vegetation
- Reducing timber stands
- Mulching wood waste.



Technical Description:

The **AHWI FM600 Forestry Mulcher** is an attachment for tractors with three point linkage and PTO drive. The main gearbox divides the power to both sides of the power belt driven rotor. The rotor is tipped with fixed carbide hammers, which are individually replaceable. A hydraulic operated follow-up and protecting flap provides efficient after-mulching. The FM600 standard model is equipped with a synchronization control for the gearbox.

Accessories:

Fixed or hydraulically operated push-bar with or without teeth, hydraulic fork, hydraulic top-link, third counter blade with wearing teeth, torque safety, skids for deeper grinding.

Options:

Rotor drive hydraulic or with mounted engine, different working widths and rotor models.

Technical Data:

PTO Power	104–149 kW	140–200 hp
Tractor Power	112–160 kW	150–240 hp
Working width standard	2300 mm	
Drive speed	1000 rev/min	
Overall width	2700 mm	
Rotor diameter	600 mm	
Weight	2790 kg	



FOUR tool choices to match your grinding requirements



Double carbide



Stone tool



Single carbide



Chipper knife