

Applications:

- Land clearing
- Forestry
- Orchard cleanup and removal
- Wetland restoration
- Bushfire brush reduction
- Landscaping
- Site-preparation

Functions:

- Slash reduction
- Recreating trails
- Land clearing
- Mulching slash piles
- Tree stump grinding
- Brush cutting
- Orchard pruning
- Grinding material into the soil.



Technical Description:

The FTX 100-L is capable of operating a number of skid steer attachments including the FM500HSS hydraulic mulchers, the BushHog bunching shear and StumpHog stump grinder, as well as rotary mowers, buckets and grapples.

Power is supplied from a Kubota diesel rated at 97 hp with maximum rated torque of 240 ft-lbs at 1500 rpm.

High hydraulic flow pressure enables attachments to be operated at optimum performance.

For maximum safety, pressurised cab (airconditioned) with forestry door is fitted as standard, with additional options for protection to suit applications.

Wide steel tracks ensure excellent traction with low ground pressure.

Technical Data:

Engine power	72 kW	97 hp
Torque	324 Nm	240 ft-lb
Length (tractor only)	3289 mm	129.5"
Width (tractor only)	1803 mm	71"
Weight (with FM500HSS)	6464 kg	14,250 lb
Hi-flow hydraulic pressure	400 bar	5800 psi
High flow	148 l/min	39 USgpm
Auxiliary pressure	234 bar	3400 psi
Auxiliary flow	72 l/min	19 USgpm
Speed (low range)	5.3 km/h	3.3 mph
Speed (high range)	9.3 km/h	5.8 mph

INSIST ON AN AHWI!