

## Applications:

- Landscaping
- Farming
- Tree nurseries
- Grinding vegetation
- Deep grinding - 400–500 mm
- Grinding heavy clay
- Plant bed preparation
- Stump grinding in orchards.



## Technical Description:

The **AHWI RF1000 Rotavator** is designed for tractors with three point linkages and PTO power from 200 to 350 hp. The rotor is driven mechanically on two sides via power belts and a divider gearbox. Rotavating depth can be adjusted by the lifting gear and hydraulic top link. The rotor is equipped with carbide-tipped tools. All wearing parts are attached by bolts and are easy to exchange.

AHWI Rotavators are ideal for grinding plant rows in nurseries, as well as mixing soil additives into the ground. All models feature a 2000 mm working width. Working depths of up to 500 mm enable excellent soil cultivation.

AHWI rotavators require a tractor fitted with a creeper gear in order to guarantee optimum performance.

## Accessories:

Post compacting roller.

## Technical Data:

|                |              |            |
|----------------|--------------|------------|
| PTO Power      | 150–261 kW   | 200–350 hp |
| Working width  | 2000 mm      |            |
| Rotor diameter | 1000 mm      |            |
| No of tools    | 64           |            |
| Working depth  | up to 500 mm |            |
| Weight         | 4900 kg      |            |