



RF800 Rotavator

Applications:

- Landscaping
- Farming
- Tree nurseries
- Grinding vegetation
- Deep grinding - 300–400 mm
- Grinding heavy clay
- Plant bed preparation
- Stump grinding in orchards.



Technical Description:

The **AHWI RF800 Rotavator** is designed for tractors with three point linkages and PTO power from 150 to 250 hp. The rotor is driven mechanically on two sides via power belts and a divider gearbox. Rotavating depth can be adjusted by the lifting gear and hydraulic top link. The rotor is equipped with carbide-tipped tools. All wearing parts are attached by bolts and are easy to exchange.

AHWI Rotavators are ideal for grinding plant rows in nurseries, as well as mixing soil additives into the ground. All models feature a 2000 mm working width. Working depths of up to 400 mm enable excellent soil cultivation.

AHWI rotavators require a tractor fitted with a creeper gear in order to guarantee optimum performance.

Accessories:

Post compacting roller.

Technical Data:

| | | |
|----------------|--------------|------------|
| PTO Power | 112–186 kW | 150–250 hp |
| Working width | 2000 mm | |
| Rotor diameter | 800 mm | |
| No of tools | 48 | |
| Working depth | up to 400 mm | |
| Weight | 3400 kg | |



AHWI Australia Pty Ltd
14 Clapham Street, Beckenham
Western Australia 6107
Telephone: (08) 9258 9333
Fax: (08) 9258 9111
Email: sales@ahwi.com.au

Authorised Distributor